

weight kg/sheet

PRODUCT RANGE <i>Gama de producción</i>								
thickness mm	commercial sizes mm							
	1000 x 2000	1250 x 2500	1250 x 3000	1500 x 3000	1500 x 4000	2000 x 4000	1500 x 6000	2000 x 6000
0,8	13	20	24	29	38		58	
1,0	16	25	30	36	48		72	
1,2	19	30	36	43	58		86	
1,5	24	37	45	54	72	96	108	144
2,0	32	50	60	72	96	128	144	192
2,5	40	63	75	90	120	160	180	240
3,0	48	75	90	108	144	192	216	288
4,0	64	100	120	144	192	256	288	384
5,0						320		480
6,0						384		576

Standard delivery program - Programa standard suministro

MANUFACTURING STANDARD <i>Norma de fabricación</i>	FINISH <i>Acabado</i>	PRODUCT DESIGNATION <i>Designación de producto</i>	GRADE <i>Calidad</i>			
EN 10088-2 ASTM A240, A480	2B Annealed pickled and skinpassed <i>Recocido, decapado y skinpasado</i>	Stainless steel flat products for general purposes <i>Productos planos de acero inoxidable para usos generales</i>	Austenitic	<i>Austeníticos</i>	Ferritic	<i>Ferríticos</i>
			EN	AISI	EN	AISI
			1.4301	304	1.4016	430
			1.4307	304L	1.4512	409LI
			1.4541	321	1.4510	439L
			1.4404	316L	1.4509	441
1.4571	316Ti	1.4521	444			
EN 10088-4 (CE marking)	2B Annealed pickled and skinpassed <i>Recocido, decapado y skinpasado</i>	Stainless steel flat products for construction purposes <i>Productos planos de acero inoxidable para usos generales</i>	Austenitic	<i>Austeníticos</i>	Ferritic	<i>Ferríticos</i>
			EN	AISI	EN	AISI
			1.4301	304	1.4016	430
			1.4307	304L	1.4512	409LI
			1.4541	321	1.4510	439L
			1.4404	316L	1.4509	441
1.4571	316Ti	1.4521	444			
EN 10028-7 ASTM A240, A480 (AD 2000 W2/W10) (PED 2014/68/EU)	2B Annealed pickled and skinpassed <i>Recocido, decapado y skinpasado</i>	Stainless steel flat products for pressure purposes <i>Productos planos de acero inoxidable para usos generales</i>	Austenitic	<i>Austeníticos</i>		
			EN	AISI		
			1.4301	304		
			1.4307	304L		
			1.4541	321		
			1.4404	316L		
1.4571	316Ti					

Supply conditions - *Condiciones de suministro*

- Dimensional tolerances according to EN ISO 9445-2 (and other equivalent international norms)
Tolerancias dimensionales según la norma EN ISO 9445-2 (y otras normas internacionales equivalentes)
- Special tolerances upon request *Tolerancias especiales bajo pedido*
- Marking on the B-Side *Marcado en lado inferior*
- Control documents 2.2, 3.1, 3.2 according to EN 10204 *Documentos de control 2.2, 3.1, 3.2 según la norma EN 10204*
- 220/240/320/400 grit polishing, scotch brite brushing, duplo and protective film suitable for fiber laser cutting
Bajo pedido: satinado 220/240/320, acabado scotch brite y película protectora adecuada para el corte láser
- With or without paper interleave *Con o sin papel intercalado*

2 cut to length line

1 Cold rolled Cut-to-length line
(till 2,000 mm width)

2 Cold rolled Cut-to-length lines
(till 2,000 mm width)

150,000 t/y
total manufacturing
capacity hot rolled
and cold rolled sheets

CR2000

**PRODUCT RANGE
EXTENSION**

sizes available on stock
width 2000 mm